



# QY25K5-II Truck Crane




## Brief introduction



25 t



40 m



47.4 m



**CAMC VIAL**

Ruta 40 y Calle 7, SAN JUAN - ARGENTINA



(+54-264) 4262275



**ARGENTINA**

+54-2644998650



[info@camcvial.com.ar](mailto:info@camcvial.com.ar)

**QY25K5-II** Truck crane is widely used for the lifting operations in general engineering projects, such as construction site, urban renewal, communication and transportation, ports, bridge, oilfields and mine, and complex working environments.




# QY25K5-II

- 5-section boom of 40.0 m with octagonal cross section is adopted; the max. lifting load is 25 t; the max. lifting height is 47.4 m; the max. working radius is 32 m.

- Load sensitive hydraulic system controlled by pilot hydraulic fluid, which brings stable performance and lower power **consumption**.





#### Slewing mechanism

- 单排四点接触球外齿式回转支承，360度回转
- Single-row four-point ball contact external tooth slewing ring, may continuously slew 360°.
- 先导式负载敏感液压系统
- Load sensitive hydraulic system controlled by pilot hydraulic fluid
- 具有动力控制或自由回转的功能，可无级调速
- Power control and free-sliding function are available, and speed may be infinitely regulated
- 回转速度为0-2.5r/min
- Slewing speed 0-2.5r/min



# QY25K5-II



## Super lifting performance

- 五节 八边形 40米主臂，双缸绳排伸缩机构，基本臂最大起重力矩961kN.m，最长主臂起重力矩553kN.m；  
■ 5-section boom of 40 m with octagonal cross section; double-cylinder plus ropes telescoping mechanism ; max load moment of base boom is 961 kN.m , and that is 553 kN.m of fully extended boom.
- 先进的嵌入式臂头，结构件强度大，下滑块面积大，受力状况更好，伸缩更平稳。  
■ Advanced build-in boom head, strong structural members and lower sliders with larger area contribute to better stress-bearing capacity and smooth telescoping movement.



## Mature load sensitive hydraulic system

- 先导控制负载敏感技术的成熟应用，使系统不受负载压力变化和油泵流量变化的影响，实现调速的目的，降低系统能耗，减小系统发热，延长液压系统使用寿命。  
■ With pilot controlled load sensitive technique, hydraulic system could not be influenced by variation of load pressure and flow of pumps, so as to control speed ,reduce energy consumption and heating , increase the working life.
- 独特的回转缓冲技术，使流量、压力精确控制，有效提高回转操作平稳性。  
■ Unique slewing buffer technology ensures precisely control of flow and pressure, which leading to smooth slewing movement.



## Hoisting mechanism

- 定量泵-变量马达液压系统
- Hydraulic system consisting of constant displacement pumps and variable displacement motors
- 行星齿轮减速器、常闭式制动器
- Planetary gear reducer, normally closed brake
- 最大单绳拉力为29KN
- Max. single line pull 29KN
- 最大起升速度125m/min
- Max. hoisting velocity 125m/min


## Elevating mechanism

- 单变幅油缸，可靠性高
- Single elevating cylinder, high reliability
- 使用带负载补偿功能的变幅平衡阀
- The elevating balance valve with load compensation function



#### Drive train

- 上柴发动机，额定功率221kw，最大输出扭矩1250N.m
- Shanghai diesel engine, rated power 221 kw, max. torque 1200 N.m
- 陕齿机械变速箱，软轴操纵，全同步器
- Mechanical transmission made by Shanxi Gear Factory, with synchronizer. It is manually operated through flexible shaft.
- 最高车速80Km/h，最大爬坡能力40%
- Max. travel speed 80 Km/h, Max. grade ability 40%




# QY25K5-II



**Optimum design of radiator and hydraulic valve, improving operation reliability in high temperature environment**

- 优化散热器油口布置，增大散热器功率（18KW），散热性能提升15%，满足高  
温环境下连续作业要求
- Optimize the oil port arrangement of the radiator, increase radiator power(18KW).The heat dissipation performance is increased by 15%,which meets the requirement of continuous operation in high temperature environment.





### 操纵室

#### Operator's cab

- 全人机工学工作空间设计,作业更舒适,安全
- Ergonomically designed working space makes operation safer and more comfortable



# QY25K5-II

## Large arc Operator's cab

- 大圆弧玻璃，装有安全玻璃和顶部保护栏
- Large arc glass, safety glass and top guard bar.



- 外开式车门、可调式座椅
- Swing-out door and adjustable seat



## automatic moment limiter

- 配有力矩限制器，液晶显示器可清晰直观地以文字和图形方式显示起重机作业参数，使各种工况一目了然；
- Equipped with load moment limiter, with LCD display, crane operation parameters can be displayed visually and clearly in text and graphic way



- 安全保护、吊装动作、操纵环境三个区域,控制便捷
- Three control areas for safety protection, hoisting operation and operating environment bring convenient control